Technical Data 600

1 1 1 DC 31	
Industry PC with	Integrated PLC
	■ Integrated CNC (with SCHMIDT* ServoPress / TorquePress)
	 Intelligent process control
	Diagnosis and service functions
	■ Linux operating system
Drive	Solid State Drive
Field bus	CANopen with possibility to connect:
	- 1 force/stroke monitored SCHMIDT* Manual-Press 3xx, 1 SCHMIDT* (Hydro)PneumaticPress, 1 SCHMIDT* Elec-
	tricPress or 1 SCHMIDT* ServoPress / TorquePress
	- SCHMIDT* PRC Gateway
	- CANopen Compact box
	■ EtherNet TCP/IP
	PROFIBUS (optionally via external CANopen/PROFIBUS-Gateway) 16 Byte input/output data
	PROFINET (optionally via external CANopen/PROFINET-Gateway) 16 Byte input/output data
	■ EtherCAT (optionally via external CANopen/ EtherCAT-Gateway) 16 Byte input/output data
Interfaces	■ EtherNet (10 / 100 MBit)
	■ 2 x USB
Panel with	 Intuitive user interface
	 Diagnosis and service functions
Screen	■ Integrated 7" widescreen TFT display (800 x 480) with touchscreen
Power supply	■ 24 V DC with integrated UPS
Assembly	Mech. adaption VESA 75 for optional table or wall fixture as well as fixture for housing